



Environmental Impact Assessment for Spatial Data Analysis in Disaster Management Using Machine Learning Multi-Criteria Resources

K. M. Ashifa¹ · Jobi Babu² · Mehdi Safaei³ · Thangaraja Arumugam⁴

Received: 20 February 2024 / Revised: 19 July 2024 / Accepted: 12 August 2024 / Published online: 19 August 2024
© The Author(s), under exclusive licence to Springer Nature Switzerland AG 2024

Abstract

Many nations have created their own frameworks for disaster risk management (DRM) in response to the rising frequency of catastrophes that cause significant losses. Finding shelter is one of the most pressing demands of anyone impacted by a disaster. While the abundance of catastrophe data is already assisting in the saving of lives, it is necessary to quickly combine a broad variety of data in order to detect building damages, determine the need for shelter, and choose the best locations to set up emergency shelters or settlements. This research suggests a machine learning (ML) approach that seeks to fuse as well as quickly evaluate multimodal data in order to fill this gap and advance complete evaluations. This study suggests a unique approach to managing environmental disasters that is based on the analysis of geographical data using a machine learning model. Here, the input is a geospatial picture of a region that frequently experiences disasters, which is then smoothed and noise-removed. Then, a fuzzy clustering-based deep spatial reinforcement model (FCDSR) was used to choose the characteristics of the processed data. Multimodal Dirichlet allocation-based LSTM (long short-term memory) logistic correspondence algorithm (MDALLCA) was used to extract the chosen features. For various catastrophe datasets, experimental analysis is done in terms of prediction accuracy, precision, F-measure, and ROC. Our findings indicate possible locations with a high density of impacted people as well as infrastructure damage during the course of the crisis.

Keywords Environmental disaster management · Spatial data analysis · Machine learning · Fuzzy clustering · LSTM correspondence algorithm

1 Introduction

Disasters are occurring more often, and the enormous human and economic losses they cause are becoming a worldwide phenomenon. The sustainability of the nations' long-term economic and social progress is gravely threatened by the direct losses. These losses will worsen as more people and infrastructure are affected by them due to the fast

urbanization [1]. Due to the high intensity of the damage caused by disasters in urban settings, novel advanced preventative measures for disaster risk management (DRM) as well as disaster risk reduction (DRR) must be developed and put into practice. National frameworks for disaster management have been created by individual states all around the world. A few nations have directed the reaction to a wide range of calamities and crises, for instance, the USA and Germany, while others have applied a particular provincial methodology, e.g., in Pacific nations and Andean nations [2]. Europe has efficient progress in developing a legal framework to lessen the likelihood of disasters and to strengthen existing ones in response to new threats [3]. Notwithstanding, public structures are very unmistakable, focussing on various viewpoints, and it turns out to be somewhat hard to assess and analyze the geospatial parts. In this manner, laying out normal evaluation standards utilizing geospatial information would assist with understanding, analyze and refresh existing structures, and lay out new ones. A typical methodology could be to inspect the substance of

✉ K. M. Ashifa
akariveliparambil@gelisim.edu.tr; ashifakattur@gmail.com

¹ Faculty of Health Science, Istanbul Gelisim University, Istanbul, Turkey

² School of Social Work, Marian College Kuttikkanam (Autonomous), Kuttikkanam, Kerala, India

³ Faculty of Economics, Administrative and Social Sciences, Logistics Management Department, Istanbul Gelisim University, Istanbul, Turkey

⁴ Business School, Vellore Institute of Technology, Chennai, India

multilaterally acknowledged DRM structures as well as track down a bunch of measures with a bigger potential of customary worthiness. Multilateral frameworks for DRM, such as Sendai Framework as well as United Nations Committee of Experts on Global Geospatial Information Management (UNGIM) method Framework on Geospatial data as well as Services for Disasters [4], include priorities for everything from governance to technical issues. Accurate and up-to-date spatial data are needed to quickly respond to a disaster as well as develop adequate evacuation as well as recovery plans. It means quite a bit to know the area, as well as to follow and examine detached and dynamic dangers all together recognize and distinguish the potential risks and perils in time [5]. Some of the time, it is important to join and incorporate information from various information sources. For instance, breaking down coupled satellite symbolism, drone symbolism, and seismic sensor data might be required. Furthermore, disaster management frequently necessitates real-time or near-real-time data analysis, which is a challenging manual task. Such and comparable issues can be tended to by applying techniques for man-made brainpower. Computerized reasoning calculations, that mirror human knowledge, have become exceptionally well known among explores managing various assignments in a debacle the executives [6].

2 Related Works

As of late, GeoAI was proposed as a system for dissecting data-driven issues in geographic data science. GeoAI plans to coordinate man-made brainpower, specifically profound learning strategies, with geospatial large information and superior execution registering to explore geospatial issues. In GeoAI, spatially express models are seen as a critical examination course [7]. Those models satisfy somewhere around one of these four necessities: The models incorporate spatial concepts in their implementation, they have a spatial representation of the studied phenomena, and they have several spatial input and output formats [8]. When the investigated phenomena are moved, the results do not remain unchanged. It has not yet been thoroughly reviewed how to move from broad ML models to building more complicated ones and then defining precise processes to build spatially explicit models. As far as the level of maximum disturbing wind speed, depth of the inflow layer, and the depth of the blended layer, Creator [9] defined many level scales in the typhoon limit layer. They analyzed hundreds of GPS dropsondes launched by aircraft and found that the thermodynamical and dynamical boundary layer thicknesses are distinctly distinct. They also observed that as distance from the tempest community is reduced, the level scales of the dynamical and thermodynamic limit layers frequently


decrease. These findings were integrated into the operational hurricane weather research and forecasting (HWRF) method [10]. In addition, expectation results demonstrated significant improvements in reenacted storm size, surface inflow point, close surface breeze profile, and kinematic limit layer levels in simulations completed with superior application of material science [11]. Automating such processes also makes it easy to adapt to evolving crisis conditions [12]. By sharing geographic and contextual information, people utilize social media as a tool to solicit assistance as well as coordinate efforts [14]. One of the most frequently observed trends is that during times of crisis, the public seeks out information more frequently [13]. Virtual entertainment assumes a significant part in emergency correspondence by empowering data spread to a more extensive crowd, sending and getting crisis cautions, controlling data dissemination, teaming up with crisis responders, and making situational mindfulness [15]. The usage of online entertainment in open data looking for has been assessed in an assortment of catastrophe occasions, for example, the spread of the Zika infection [16], the fell span in Minnesota, the Mexican medication wars, the Bedouin Spring, the Haiti tremor, and various flood occasions. Even though automated event detection in crisis situations has made significant progress, it is still difficult to extract fine-grained event-related data like affected individuals as well as damaged infrastructure [17, 18]. To further develop the occasion discovery, various methodologies have been presented. For instance, the creator [19] dissected the substance and sort of data as well as the wellspring of data by joining lexical examination with client profiling. Work [20] found that semantic as well as stylistic features derived from metadata improve recall, while lexical features aid in improving precision.

3 System Model

The structure for integrating data from several sources for disaster management is shown in Fig. 1. Our framework consists of three processes or modules: data gathering, data processing, and data geovisual analysis. Each module is described in depth below.

Preprocessing Every information methodology was pre-processed to eliminate exceptions (outrageous high/low qualities) and concentrate its mathematical qualities. Using the one-hot encoding technique, alphabetical and alphabetical data were converted into numerical values. A self-referential process was used to translate each image into an n-dimensional numerical vector in order to extract numerical features from the satellite images. This approach creates a dictionary of every word found in the data and gives each one a number that encodes it as an integer.

Fig. 1 Proposed disaster management architecture



Diminution of Dimension The following three data classes will have their dimensions reduced: environment types, regular assets, satellite pictures. The t-SNE calculation can catch a significant part of the neighborhood construction of high-layered information while uncovering the worldwide design. In order to convert each n-dimensional vector list into a one-dimensional vector, we set the Perplexity within t-SNE to 100.

Normalization Positive as well as negative skewness of data is reduced by logarithmic transformation (LT). LT narrows the gap between values by taking into account the absolute difference between values of comparable performance. Interpretation of differences between values at opposite extremes is improved by this transformation, which makes it easier to distinguish the minute differences that exist across all performance ranges.

Standardization This adjusts the values of each attribute to have a sample variance of one and a mean of zero. This strategy permits us to work related to factors that address various modalities. We first determine the standardization $(= (x - \text{mean}(x)) /)$ before calculating the standard deviation $(.)$. They are now prepared to be fused into a vector with 19 dimensions that describe each natural disaster after all attributes have been standardized. The natural disaster is represented in its entirety by each attribute.

3.1 Fuzzy Clustering–Based Deep Spatial Reinforcement Model

Assume that there are n samples in the dataset $(X = \times 1, \times 2, \text{ and } n)$, and that sample x_i has l features. To cluster the dataset

X into c groups is our aim. Let V consist of $v_1, v_2, v_3, \text{ and } v_c$, and let C consist of $c_1, c_2, v_3, \text{ and } c_c$, as the set of clusters. Stated differently, FCM allows each sample to have fuzzy memberships to many clusters. The FCM's goal-oriented purpose is by Eq. (1):

$$J_m(U, V) = \sum_{k=1}^c \sum_{i=1}^n (u_{ik})^m (d_{ik})^2 \quad (1)$$

The restrictions that must be met are by Eq. (2):

$$\begin{cases} \sum_{k=1}^c u_{ik} = 1, & i = 1, 2, \dots, n \\ 0 \leq u_{ik} \leq 1, & i = 1, 2, \dots, n, k = 1, 2, \dots, c \\ 0 < \sum_{i=1}^n u_{ik} < n, & k = 1, 2, \dots, c, \end{cases} \quad (2)$$

Following Eq. (3), based on the Lagrange multiplier approach, determine U and V , respectively.

$$u_{ik} = \frac{1}{\sum_{j=1}^c \left(\frac{d_{ik}}{d_{jk}} \right)^{\frac{2}{m-1}}} \text{ and } v_k = \frac{\sum_{i=1}^n (u_{ik})^m x_i}{\sum_{i=1}^n (u_{ik})^m}$$

$$J_m(U, v) = \sum_{k=1}^c \sum_{i=1}^n (u_{ik})^m \|y_k - v_i\|_A^2 \quad (3)$$

Equation (4) contains the following variables:

$$\begin{aligned}
Y &= \{y_1, y_2, \dots, y_N\} \subset \mathbf{R}^n = \text{data}, \\
c &= \text{number of clusters in } Y; 2 \leq c < n, \\
m &= \text{weighting exponent}; 1 \leq m < \infty, \\
U &= \text{fuzzy } c\text{-partition of } Y; U \in M_{||} \\
v &= (v_1, v_2, \dots, v_c) = \text{vectors of centers}, \\
v_i &= (v_{i1}, v_{i2}, \dots, v_{in}) = \text{center of cluster } i, \\
\| \cdot \|_A &= \text{induced } A\text{-norm on } \mathbf{R}^n \\
A &= \text{positive-definite } (n \times n) \text{ weight matrix.}
\end{aligned} \quad (4)$$

Equation (5)'s squared distance between y_k and v_i is evaluated utilizing A-norm as

$$d_{ik}^2 = \|y_k - v_i\|_A^2 = (y_k - v_i)^T A (y_k - v_i). \quad (5)$$

The question of whether local minima of J_m are good Y clusterings is arguable since it is easy to generate data sets in which J_m minimizes globally with an ugly substructure. To mitigate this issue, several types of cluster validity functionals are frequently calculated on each 0 generated by FCM. Two of the best-known instances by Eq. (6) are the entropy and partition coefficient of OE Mfc.

$$F_c(\hat{O}) = \sum_{k=1}^N \sum_{i=1}^c (\hat{u}_{ik})^2 / N$$

$$H_c(\hat{U}) = - \sum_{k=1}^N \sum_{i=1}^c (\hat{u}_{ik} \log_{\sigma}(\hat{u}_{ik})) / N.$$

$$\begin{aligned}
F_c = 1 &\iff H_c = 0 \iff \hat{U} \in M_c \text{ is hard;} \\
F_c = 1/c &\iff H_c = \log_a(c) \iff \hat{U} = [1/c]; \\
\frac{1}{c} &\leq F_c \leq 1; 0 \leq H_c \leq \log_a(c).
\end{aligned} \quad (6)$$

FCM program listed below evaluates F , H , and $(1 - F)$, the latter quantity owing to inequality $(1 - F) < H$ for $\hat{U} \notin M_c$ (when $a = e = 2.71 \dots$).

We look into the categorized earthquake-related Tweets' spatial hotspots. As a result, we make a standard grid with cells that are 1 km by 1 km in size and summarise each Tweet inside of a grid cell. A number of points in the study area as well as its size were taken into account when determining the grid size. In more detail, we applied a method from the field of point pattern analysis, which considers the size of research area as well as the number of points to estimate ideal cell width by Eq. (7):

$$l = \sqrt{2 \frac{A}{n}} \quad (7)$$

where n is the number of points in research area, A is the study area's size, and l is the grid cell's side length. For each feature extraction task, the label field can be found by

maximizing the posterior probability distribution shown in Eq. (8).

$$\begin{aligned}
E(|y_t \cap A_1| | \gamma_{t+\Delta t} \cap A_2|) &= \int_{A_3} \int_{A_t} k_{t,\perp}(x_1, x_2) dx_2 dx_1 \\
&+ \int_{A_1 \cap A_s} k_{t,L}(x) dx, \frac{d}{dt} k_t(\eta) = (L^\Delta k_t)(\eta),
\end{aligned} \quad (8)$$

$$\frac{d}{dt} k_t^{(1)}(x) = -mk_2^{(d)}(x) - \int_{R^d} a^-(x-y)k_t^{(2)}(x,y)dy + \int_{R^d} a^+(x-y)k_t^{(1)}(y)dy. \quad (9)$$

Equations (10), (11), and (12) also meet the following Markovianity property:

$$\begin{aligned}
p(X_{st} = x_{st} | X_{qr} = x_{qr}, s \neq q, t \neq r, \forall (s, t), (q, r) \in V) = \\
p(X_{st} = x_{st} | X_{qr} = x_{qr}, s \neq q, t \neq r, (q, r) \in \eta_{sr})
\end{aligned} \quad (10)$$

$$z^g = \frac{N^g}{\sum_{i=1}^N f\left(\frac{n_i^{\text{eff}}}{s_i}\right) (n_i^g)^{\text{eff}}} \quad (11)$$

$$(n_i^g)^{\text{eff}} = \sum_j \left[(1 - p^g) \delta_{ij} + p^g R_{ji}^g \right] n_j^g.$$

$$f(x) = 1 + (1 - e^{-\xi x})$$

$$n_{j \rightarrow i}^{m,h}(t) = n_j^h \rho_j^{m,h}(t) \left[(1 - p^h) \delta_{ij} + p^h R_{ji}^h \right], m \in \{A, I\} \quad (12)$$

Prior probability $P(X_t = x_t, \theta)$ is of form and conforms to Gibbs distribution by Eq. (13).

$$P(X_t = x_t) = e^{-U(x_t, \theta)} = e^{[-\sum_{s,t} [V_{sc}(x_{st}, x_{qt}) + V_{tec}(x_{st}, x_{qr}) + V_{tec}(x_{st}, x_{er})]]} \quad (13)$$

$$P(X_t = x_t) = e^{-U(x_t, \theta)} = e^{[-\sum_{ccC} [V_{sc}(x_{st}, x_{qt}) + V_{tec}(x_{st}, x_{qr})]]} \quad (14)$$

The corresponding edgeless method is given by Eq. (15):

$$P(X_t = x_t) = e^{-U(x_t, \theta)} = e^{[-\sum_{ccC} [V_{sc}(x_{st}, x_{qt}) + V_{tec}(x_{st}, x_{qr})]]} \quad (15)$$

The likelihood function $P(Y_t = y_t | X_t = x_t)$ can be expressed as Eq. (16):

$$\begin{aligned}
P(Y_t = y_t | X_t = x_t) &= P(y_t = x_t + n | X_t = x_t, \theta) = \\
&P(N = y_t - x_t | X_t = x_t, \theta)
\end{aligned} \quad (16)$$

Thus, $P(Y_t = y_t | X_t = x_t)$ can be expressed as Eq. (17):

$$P(N = y_t - x_t | X_t, \theta) = \frac{1}{\sqrt{(2\pi)^f \det[k]}} e^{-\frac{1}{2}(y_t - x_t)^T k^{-1} (y_t - x_t)} \quad (17)$$

Agent gets a state at each time step t and generates a corresponding action $\pi(a_t - s_t)$. The purpose of agents is to

create an action plan that maximizes the projected cumulative return of the form, or objective function, as defined by Eq. (18).

$$J(\pi) := \sum_{t=0}^T \mathbb{E}_{(s_t, a_t)} [\gamma^t r(s_t, a_t)] \quad (18)$$

$$\max_{\theta \in \mathbb{R}^d} J(\theta). \quad (19)$$

3.2 Multimodal Dirichlet Allocation–Based LSTM Logistic Correspondence Algorithm

LDA assumes that one or more topics z are contained in every document d of a set of documents D . These topics are again described by a probability distribution of single words w , which is model's only observed variable. As a result, topic's multinomial word distribution is represented by the latent variable. The document's multinomial topic distribution is the other latent variable. α , furthermore, and β are two fixation boundaries— α addresses earlier information about the circulation of subjects in a report, while β contains earlier information about the conveyance of words in a point. The distribution of topics across the document is smoother when the value is higher, while the concentration of topics is higher when the value is lower, especially when it is less than zero. The latent variables z propose a value of $50/T$ for these variables, which are produced during the process but appear to have a best working value of 0.0001 in our case. This is reasonable given the nature of our Twitter dataset, which assumes that every Tweet contains only one topic due to its short length (up to 140 characters). As a result, when 1, probability distribution is more concentrated. In our review, 1000 passes convey the best outcomes—a bigger number does not further develop the learning impact anymore and however diminishes execution. The quantity of points unequivocally impacts the subject word circulations concerning the granularity of the points. In this way, a lower number of subjects prompts bigger points (containing more words), while a larger number of themes prompts more modest points (containing less words). This is, in essence, a trade-off between generation of distinct as well as significant topics and minimization of information loss caused by high granularity. A document–topic matrix is created by LDA (linear discriminant analysis), which contains topics and probabilities for every document. This indicates that a single Tweet may contain multiple topics. In a following stage, the idle points must be semantically deciphered to distinguish disaster-related or harm-related Tweets. One issue throughout our examination was the extraction of harm-related Tweets in light of the fact that no such point was created in the primary LDA run. Hence, we applied flowed

LDA method, for example, we ran LDA a second time just on quake-related Tweets.

The relationship of past words with the planned result might influence the significance of and potential derivations that can be produced using last-option words. This connection of previous words with result ought to be carried on to the following hubs to catch the consecutive idea of sentences. Data that is being learned as well as stored in a feature vector in a “vanilla” RNN changes irregularly. Because of disappearing slope issue, the heaviness of the brain network gets a vanishingly little extent of the inclination of the misfortune which restricts the growing experience. Accordingly, the method involved with learning loads might be slow or try and stop. In this way, a basic and unobtrusive RNN is not equipped for recalling the elements learned for significant time frames. This for the most part influences the general exactness of text arrangement errands.

LSTMs and their varieties are broadly utilized in characterization errands that need longer recollections, like picture grouping, text order, and time-series examination. The conditions (4)–(9) give a short outline of a LSTM hub and numerical foundation of a LSTM hub. LSTM hub is applied to tensors x_t and h_{t-1} in which x_t addresses info, and h_{t-1} addresses the secret condition of past LSTM hub in layer. Sigmoid function is $s(\cdot)$ in Eq. (20), and $\tanh(x)$ is a hyperbolic tangent function. Hyperbolic tangent function

$$\tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}} \quad (20)$$

Input gate, forget gate, output gate, and cell update gate values are formed from input and hidden state vectors by weight matrices W and U . These gates allow LSTMs to provide a method for forgetting previously learned features from earlier nodes that are no longer applicable. These gates compute the output of an LSTM node, where $\circ$ operator stands for an element-wise product. The cell state and hidden state are then sent together with the next LSTM node and layer in NN architecture. The input gate of an LSTM node by Eq. (21)

$$i_t = \sigma(W^{(i)}x_t + U^{(i)}h_{t-1}) \quad (21)$$

Forget the LSTM node's gate by Eq. (22)

$$f_t = \sigma(W^{(f)}x_t + U^{(f)}h_{t-1}) \quad (22)$$

LSTM node's output gate by Eq. (23)

$$o_t = \sigma(W^{(o)}x_t + U^{(o)}h_{t-1}) \quad (23)$$

LSTM node's cell update gate by Eq. (24)

$$\tilde{c}_t = \tanh(W^{(c)}x_t + U^{(c)}h_{t-1}) \quad (24)$$

State of an LSTM node's cell by Eq. (25)

$$c_t = f_t \circ c_{t-1} + i_t \circ \tilde{c}_{t-1}. \quad (25)$$

An LSTM node's hidden state by Eq. (26)

$$h_t = o_t \circ \tanh(c_t) \quad (26)$$

In addition to LSTM networks and other layers like embedding and dropout layers, DNN described here relies on these as well. We utilized the binary cross-entropy (Eq. (2)) and sigmoid (Eq. (1)) functions in LSTM. We also assessed categorical cross-entropy function, which did outperform binary cross-entropy function in terms of performance. Therefore, we choose not to present categorical cross-entropy function's findings. Consider forest fire training dataset $D = x_i; y f g_i N i$, which has n conditioning variables, N data samples, and input data of x_i Rn. The 10 input variables listed above were used in our study, and output y_k 1, 0 indicates a division into two classes, forest fire and non-forest fire. Using the above equation, LogitBoost creates an ensemble model with m tree-based classifiers by Eq. (27):

$$f^{(m)} = \operatorname{argmin}_f \sum_{i=1}^n w_i^{(m)} \left(z_i^{(m)} - f(x_i) \right)^2$$

$$w_i^{(m)} = p^{(m-1)} \cdot (1 - p^{(m-1)})$$

$$z_i^{(m)} = \frac{y_i - p^{(m-1)}(x_i)}{w_i^{(m)}} \quad (27)$$

where $p(x_i)$ denotes estimations of probability. Equation (28) is used to update the ensemble model, while Eq. (8) is used to compute the class probability.

$$F^{(m)}(x_i) = \frac{1}{1 + e^{-2F^{(m)}(x_i)}} \quad (28)$$

In spite of its obvious effortlessness, this classifier accomplishes a cutthroat outcome with helping. Subsets were created using LogitBoost, which were then used to construct the decision stump-based base classifier. The number of subgroups varied from one to one hundred in a trial-and-error test, after which the classification accuracy of the final model was calculated. This was done since the amount of basic classifiers affects how well the model performs. The results showed that the 90-subset model had the highest classification accuracy. As a result, the 90 decision stump classifiers served as foundation for best LogitBoost ensemble method in our investigation.

The change from scores to positioning is considered a standardization interaction. The positioning vectors of multitude of occasions in dataset are linked to build $N \times 2C2$

pointer framework $M = [R1, R2, \dots, RN]$, where R_k is the positioning vector of occurrence k and N is the absolute number of examples in dataset. In this way, every idea at a specific positioning is changed to a vector in nonstop subspace, which can best address correspondence among preparation information. Consequently, SVD (singular value decomposition) on M indicator matrix serves as the foundation of the MCA training process by Eq. (29):

$$\operatorname{diag}(\operatorname{row})^{-\frac{1}{2}} \left(M - \operatorname{row} \cdot F^{(m-1)}(x_i) + \frac{1}{2} f^{(m)}(x_i) \right) \quad (29)$$

The following is how desired concept representation is obtained by Eq. (30):

$$T = \operatorname{diag}(\operatorname{row})^{-\frac{1}{2}} U \Sigma \quad (30)$$

Thus, by using this concept representation T , continuous features of initial indicator matrix M can be obtained as follows by Eq. (31):

$$F = T.M \quad (31)$$

Changed portrayal F is then utilized to prepare method in preparation cycle, while grouping results are deduced from consistent elements F of the test information in testing system. We consolidated tweet post-date in tweet vectors to uncover connection between a tweet's post-date and its pertinence with flooding as well as outrageous climate occasions. Datetime tagging can be carried out at a variety of temporal granularities, including minute, hour, day, and week. Despite the fact that floods might happen abruptly, their effect, for example, flood immersion, frequently endures days, weeks, and in certain cases longer time spans. Accordingly, we planned dates between 29 August 2017 and 17 October 2017 on to a number scale somewhere in the range of 1 and 50, and we attached the whole numbers into the element vector.

4 Results and Discussion

Topic modeling, accuracy assessment, and spatial hot spot analysis are the outcomes of our application of the methodology described in the preceding section. These findings are presented in this section.

Dataset The information utilized in this study were pre-tremor and postearthquake remote detecting pictures from Landsat-8 and Sentinel2, all the more definitively two pictures from Landsat-8, comprised of eight multispectral groups with a spatial goal of 30 m, and two Sentinel pictures with a spatial goal of 10 m and three noticeable transmission capacity.

Earthquake at Amatrice On 24 August 2016, a seismic tremor with a greatness of 6.2 hit focal Italy with focal point near Accumoli, Italy. More than 290 people died in the earthquake, which also severely damaged the city of Amatrice and other nearby towns. Between August 17 and September 9, 2016, we gathered 48,992 georeferenced Tweets that were within the World Geodetic System 1984 bounding box. On August 24, 2016, the earthquake that struck central Italy occurred at 03:36:32, resulting in a peak in time series of number of tweets sent per hour. This peak corresponds to the hour that the earthquake occurred.

To assess conveyability to other seismic tremor occasions in another worldwide area, we broke down the quake in Amatrice, Italy. This is particularly intriguing given that Italian is the official language in Italy, as opposed to English in the United States. As a result, we can learn from the Amatrice earthquake whether approach works in other languages, for other natural disasters, and on a different continent. Using python package Polyglot, we identified languages utilized in Tweet corpus. We found that approximately 15.4% were written in Italian and 57.1% were written in English. 23.6% of the Tweets' language could not be automatically identified. We anticipated more Italian than English tweets, but diverse language distribution continues to be a challenge. Spatial binning is a method of visualizing data that involves grouping data points into shapes like triangles, rectangles, or hexagons. Hexagons have been demonstrated to be the most reasonable shape to utilize. Despite the fact that the Amatrice earthquake was one of Italy's strongest, nearby urban centers show more activity than the affected region.

Tropical Storm Harvey Tropical storm Harvey made landfall on 25 August 2017, near Houston, Texas, which is home to 2,000,000 occupants. Heavy rain fell in the area as Hurricane Harvey slowed down, causing horrendous damage worth \$125 billion and 68 deaths. As opposed to tremors, storms do not cause an unexpected expansion in Tweets since they are sluggish as well as checked days before landfall. By looking at the quantity of Tweets each hour in a week in which Storm Harvey happened with prior week, we see that the general number of Tweets expanded; however, there is no apparent pinnacle.

Utilizing vectorized rendition of physically named dataset, we prepared a progression of parallel classifiers. To improve the predictability of models for unrelated tweets, we included related as well as unrelated data manually classified by human coders in our training set. There were a total of 20,413 tweets in the dataset prior to any sampling, of which 7801 were manually classified as related as well as 12,612 as unrelated. Subsampled information were then parted into preparation as well as test sets in which preparation set comprised 80% and test set was 20%. From that

point forward, 12,481 preparation successions and 3121 test arrangements were utilized. The proportion of true positives as well as true negatives across all classified tweets is used to measure accuracy. While accuracy is the small part of pertinent tweets among every single applicable tweet (for example, genuine up-sides/(genuine up-sides + bogus up-sides)), review is the negligible portion of pertinent tweets over the aggregate sum of tweets (genuine up-sides/(genuine up-sides + misleading negatives)).

Table 1 shows the subject word conveyance of principal LDA emphasis for “tremor” point, in which “quake” has a likelihood of 43.30%, which is uncommonly high. Besides, words “california” and “harm” show up in this point. Outcomes introduced in Table 1 are profoundly proper to produce seismic tremor impression. In any case, in this first emphasis, no independent “harm” point was created. In this way, we applied a flowing LDA way to deal with looking at the tremor point in more detail.

Table 2 shows an analysis for various environmental datasets. Here, datasets analyzed are the Amatrice earthquake dataset and the Hurricane Harvey dataset in terms of prediction accuracy, precision, F-measure, and ROC.

Figure 2 shows a comparison of prediction accuracy for the Amatrice earthquake dataset and the Hurricane Harvey dataset. The proposed technique attained a prediction accuracy of 95%, existing RNN of 91%, and RF of 93% for the Amatrice earthquake; for the Hurricane Harvey dataset, the proposed technique attained a prediction accuracy of 96%, existing RNN of 89%, and RF of 96%.

The above Fig. 3 shows a precision comparison based on various datasets. Here, proposed technique precision of 76%, existing RNN of 74%, and RF of 75% for the Amatrice earthquake; for the Hurricane Harvey dataset proposed technique precision of 86%, existing RNN of 83%, and RF of 85% for comparison of precision.


Figure 4 shows a comparison of F-measure. Proposed technique F-measure of 75%, existing RNN of 71%, and RF of 73% for the Amatrice earthquake; for the Hurricane

Table 1 Word distribution for “earthquake” topic

Word	Probability (%)
Earthquake	43.30
California	5.90
College	1.80
Slept	2.50
Damag	2.80
White	1.70
Hope	1.20
Challenge	1.60
Report	1.60
Stand	1.20

Table 2 Comparative analysis of various environmental datasets

Dataset	Techniques	Prediction accuracy	Precision	F-measure	ROC
Amatrice earthquake	RNN	91	74	71	65
	RF	93	75	73	66
	FCDSR_DALLCA	95	76	75	71
Hurricane Harvey	RNN	89	83	83	81
	RF	93	85	85	83
	FCDSR_DALLCA	96	86	89	86

Fig. 2 Comparison of prediction accuracy

Harvey dataset proposed technique F-measure of 89%, existing RNN of 83%, and RF of 85% for Comparison of F-measure.



Figure 5 shows ROC comparison based on various datasets. Here, proposed technique ROC of 71%, existing RNN of 65%, and RF of 66% for the Amatrice earthquake; for the Hurricane Harvey dataset proposed technique ROC of 86%, existing RNN of 81%, and RF of 83% for Comparison of ROC.

Spatial binning of georeferenced Tweets in space affected by Storm Harvey shows high action in metropolitan areas, particularly in Austin, San Antonio, Houston, and Twirly doo Rouge. While Austin, San Antonio, and Rod Rouge were not affected by Storm Harvey, a large portion of the city of Houston was flooded. The dataset must be further analyzed because this visualization cannot be utilized by disaster managers to determine which areas are impacted by a disaster. Framework cells address huge problem areas of tremor-related Tweets, while polygons

behind the scenes frame authority USGS quake impression in various PGA forces. For factual approval, we overlaid USGS impression with problem areas produced by our strategy. In an initial step, we made a basic disarray lattice of framework cells matching USGS as well as Twitter impressions.


5 Conclusion

This research proposes a novel approach in environmental geospatial data analysis using machine learning–based feature selection with feature extraction. Here, the input data has been analyzed using fuzzy clustering–based deep spatial reinforcement model (FCDSR) and multimodal Dirichlet allocation–based LSTM logistic correspondence algorithm (MDALLCA). Our AI approach does not need broad deduced information about the calamity occasion (for example, catchphrases to look for), which

Fig. 3 Comparison of precision**Fig. 4** Comparison of F-measure

is a significant calculate web-based entertainment based investigation since informal communities frequently foster their own wording (hashtags, articulations, and so on.). As a result, we are able to identify and quantify events that might not be described by commonly used keywords. To

put it another way, the goal of our method is to locate the appropriate “set of words” for the analysis. A brand-new image dataset containing two hurricanes is used to evaluate the multimodal framework that has been proposed. Effectiveness as well as dominance of proposed framework in comparison to a number of existing methods is demonstrated by the experimental results. In future, proposed

Fig. 5 Comparison of ROC

dataset is reached out to contain more catastrophe occasions as well as ideas. To improve the final classification results, other modalities like meta data as well as textual data can also be used.

Author Contribution Jobi Babu: conceptualization, methodology, investigation, writing—review and editing, resources, project administration.

Mehdi Safaei: methodology, software, formal analysis, data curation, writing—review and editing, visualization.

Thangaraja Arumugam: conceptualization, methodology, investigation, writing—review and editing, supervision, funding acquisition.

Data Availability No datasets were generated or analysed during the current study.

Declarations

Ethics Approval This article does not contain any studies with animals performed by any of the authors. Ethical guidelines were strictly followed throughout the study.

Conflict of Interest The authors declare no competing interests.

References

- Ivić M (2019) Artificial intelligence and geospatial analysis in disaster management. *Int Arch Photogramm Remote Sens Spat Inf Sci* 42:161–166
- Abid SK, Sulaiman N, Chan SW, Nazir U, Abid M, Han H, ... Vega-Muñoz A (2021) Toward an integrated disaster management approach: how artificial intelligence can boost disaster management. *Sustainability* 13(22):12560
- Martínez-Álvarez F, Tien Bui D (2020) Advanced machine learning and big data analytics in remote sensing for natural hazards management. *Remote Sensing* 12(2):301
- Antoniou V, Potsiou C (2020) A deep learning method to accelerate the disaster response process. *Remote Sensing* 12(3):544
- Khan SM, Shafi I, Butt WH, Diez IDLT, Flores MAL, Galán JC, Ashraf I (2023) A systematic review of disaster management systems: approaches, challenges, and future directions. *Land* 12(8):1514
- Havas C, Resch B (2021) Portability of semantic and spatial-temporal machine learning methods to analyse social media for near-real-time disaster monitoring. *Nat Hazards* 108(3):2939–2969
- Linardos V, Drakaki M, Tzionas P, Karnavas YL (2022) Machine learning in disaster management: recent developments in methods and applications. *Mach Learn Knowl Extraction* 4(2):446
- Jaber MM, Ali MH, Abd SK, Jassim MM, Alkhayyat A, Aziz HW, Alkhuwayldee AR (2022) Predicting climate factors based on big data analytics based agricultural disaster management. *Phys Chem Earth, Parts A/B/C* 128:103243
- Subhashini R, Thomas JJ, Sivasangari A, Mohana P, Vigneshwari S, Asha P (2022) Artificial intelligence-based intelligent geospatial analysis in disaster management. In *Advances of Artificial Intelligence in a Green Energy Environment* 203–221. Academic Press. <https://doi.org/10.1016/B978-0-323-89785-3.00006-2>
- Tzavella K, Skopeliti A, Fekete A (2022) Volunteered geographic information use in crisis, emergency and disaster management: a scoping review and a web atlas. *Geo-spatial Inf Sci* 1–32. <https://doi.org/10.1080/10095020.2022.2139642>
- Linardos V (2022) A machine learning based method for automatic identification of disaster related information using Twitter data. In *Intelligent and Fuzzy Systems: Digital Acceleration and The New Normal-Proceedings of the INFUS 2022 Conference* 2:505:70. Springer Nature. https://doi.org/10.1007/978-3-031-09176-6_8

12. Sreelakshmi S, Chandra SV (2022) Machine learning for disaster management: insights from past research and future implications. In 2022 International Conference on Computing, Communication, Security and Intelligent Systems (IC3SIS) 1–7. IEEE. <https://doi.org/10.1109/IC3SIS54991.2022.9885494>
13. Rahman M, Chen N, Islam MM, Mahmud GI, Pourghasemi HR, Alam M, Dewan A (2021) Development of flood hazard map and emergency relief operation system using hydrodynamic modeling and machine learning algorithm. *J Clean Prod* 311:127594
14. Zheng Z, Zhong Y, Wang J, Ma A, Zhang L (2021) Building damage assessment for rapid disaster response with a deep object-based semantic change detection framework: from natural disasters to man-made disasters. *Remote Sens Environ* 265:112636
15. Vinod AM, Venkatesh D, Kundra D, Jayapandian N (2022) Natural disaster prediction by using image based deep learning and machine learning. In Second International Conference on Image Processing and Capsule Networks: ICIPCN 2021 2:56–66. Springer International Publishing. https://doi.org/10.1007/978-3-030-84760-9_6
16. Saravanan S, Abijith D (2022) Flood susceptibility mapping of Northeast coastal districts of Tamil Nadu India using multi-source geospatial data and machine learning techniques. *Geocarto Int* 37(27):15252–15281
17. Kabiru P, Kuffer M, Sliuzas R, Vanhuysse S (2023) The relationship between multiple hazards and deprivation using open geospatial data and machine learning. *Nat Hazards* 1–35. <https://doi.org/10.1007/s11069-023-05897-z>
18. Albrecht CM, Elmegreen B, Gunawan O, Hamann HF, Klein LJ, Lu S, Schmude J (2020) Next-generation geospatial-temporal information technologies for disaster management. *IBM J Res Dev* 64(1/2):5–1
19. Casali Y, Aydin NY, Comes T (2022) Machine learning for spatial analyses in urban areas: a scoping review. *Sustain Cities Soc* 85:104050
20. Sahoh B, Choksuriwong A (2022) A proof-of-concept and feasibility analysis of using social sensors in the context of causal machine learning-based emergency management. *J Ambient Intell Humaniz Comput* 13(8):3747–3763

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Springer Nature or its licensor (e.g. a society or other partner) holds exclusive rights to this article under a publishing agreement with the author(s) or other rightsholder(s); author self-archiving of the accepted manuscript version of this article is solely governed by the terms of such publishing agreement and applicable law.